

MA500-Series Test



MA500

MA500-Series Test

Flexible and durable encoder for demanding applications.
Incremental encoder Ø30mm.

Main features

- ✓ 2 years warranty
- ✓ Superfast

Electrical Specs

Power Supply	7-35Vdc
Current Consumption	Max 40mA, without load
Output Circuit	HTL
Low Level Output Volt	<0,5 V at 20 mA load and 20°C
High Level Output Volt	Min >Vcc-2V at 20mA load and 20°C
Max Load	70 mA
Polarity Protected	✓
Transient Protected	✓

Connections

1xU Axial cable	1xLU Axial cable
2xU Radial cable	9 Axial 4-pin M8 male connector

Mating Cables

M8SR5, Snap Straight 5m 4x0,25 PUR/PUR
M8SV2, Snap Angled 2m 4x0,25 PUR/PUR
M8SV5, Snap Angled 5m 4x0,25 PUR/PUR

Signal Accuracy

Dividing Error Max	±50 el°
Channel Separation	90 ±25 el°
Max Frequency	100 kHz
Operating Temperature	-40° to +80°C

Functions

Signal	Cable	9 Connector	Mating cable M8
1	Green	3 Blue	Blue
2	Yellow	4 Black	Black
+V	Brown	1 Brown	Brown
0V	White	2 White	White
		Chassis	

Mechanical Specification

Housing	Aluminum, electrically conductive for increased interference protection
Sealing	IP67 dust and splash proof (IP66 at shaft outlet)
Bearings	Permanently greased
Bearing Load At	1 000 rpm
Bearing Axial	30N
Bearing Radial	30N
Max RPM	3 000 (12 000)
Vibration	20g 20-2000 Hz
Shock	200g at 11 ms

Other

Customization	upon request
ExternPulsmätare	akrok3

Ordering Key

Model	MA500
MA500	
Pulsrate	0200
2-1250	
Shaft	06
4-6mm	
Connection	1
Cable	
x-cable length (m)	1xU
2	

Example

MA500 - 0200 - 06 - 1 - 1xU

Model

MA500-Series Test

Article ID

MA500